



TODCO MSRP PRICE LIST

3/4" ALUMINUM COVERED DOOR

Door Ht. In Inches	DOOR OPENING WIDTH			
	Up to 48"	Over 48" Up to 72"	Over 72" Up to 90"	Over 90" Up to 96"
76	772.76	880.67	978.40	1,007.29
77	787.76	890.11	991.61	1,020.88
78	817.85	909.17	1,004.83	1,034.48
79	848.05	928.08	1,017.95	1,047.99
80	878.11	947.10	1,031.16	1,061.58
81	908.17	966.08	1,044.33	1,075.14
82	938.24	985.05	1,057.45	1,088.63
83	968.39	1,003.96	1,070.86	1,102.40
84	998.45	1,022.97	1,084.30	1,116.25
85	1,006.69	1,035.07	1,093.87	1,126.18
86	1,014.97	1,047.16	1,103.38	1,136.08
87	1,023.36	1,059.21	1,112.90	1,145.99
88	1,031.61	1,071.32	1,122.51	1,155.96
89	1,039.91	1,083.36	1,132.04	1,165.89
90	1,048.19	1,095.46	1,141.54	1,175.77
91	1,063.77	1,113.18	1,155.76	1,190.36
92	1,086.38	1,136.47	1,172.90	1,207.88
93	1,109.18	1,159.79	1,185.90	1,221.26
94	1,131.81	1,183.01	1,204.46	1,240.20
95	1,154.55	1,206.34	1,225.40	1,261.51
96	1,177.21	1,229.70	1,246.31	1,282.82
97			1,267.11	1,300.95
98			1,288.11	1,322.27
99			1,310.93	1,348.57
100			1,335.64	1,373.65
101			1,360.39	1,398.80
102			1,385.08	1,423.88
103			1,409.26	1,448.41
104			1,433.46	1,472.98
105			1,457.53	1,497.47
106			1,481.78	1,522.09
107			1,505.91	1,546.58
108			1,530.09	1,571.15
109			1,554.30	1,595.75
110			1,578.44	1,620.25
111			1,602.59	1,644.79
112			1,626.74	1,669.31


Includes:

1. .024 Pre-Painted Aluminum skin on outside only over 3/4" Marine type plywood with ToughShell™ primer coatings.
2. Bottom seal and header seal – standard.
3. Heavy Duty 1" ball bearing rollers – standard.
4. Galvanized track and hardware.
5. Safety tested custom counterbalance with dual cables.
6. TODCO Heavy Duty self-adjusting lock with secondary keeper. Standard M.S.

For larger sizes and special applications, contact the nearest TODCO factory.

For options, consult the Door Options Price List.

LUBRICATION



- Lubricate the counterbalance bearings, spring, roller hinges and lock liberally with TODCO FG Lube.
- DO NOT USE GREASE.
- Frequency of door maintenance will vary with climate conditions and door cleaning procedures. Doors which are steam cleaned on the interior face will need lubricating more often than those not cleaned by this method. Doors on equipment which will run in areas where road salts are used will require lock lubrication at closer intervals.
- Lubrication should increase with cleaning frequency.

PLEASE NOTE:

- All prices shown or quoted are for one assembled door complete with all door hardware.
- F.O.B. shipping factory.
- Effective Date: Sept. 1, 2011. Supersedes all previous Price Lists.
- Prices subject to change without notice. Surcharge may apply.
- For complete information or recommendations on specific requirements, contact your nearest TODCO plant or any of our representatives.
- High pressure wash or harsh cleaning solutions can damage door finish.