

POLARTEK™





SUPERIOR THERMAL EFFICIENCY HAS NEVER BEEN MORE ATTRACTIVE.

TODCO took a proven performer, the PolarGuard® refrigerated door, and made it even better. The new PolarTek door starts with smooth, tough, extruded hollow-core polycomposite panels for an automotive-quality appearance that even moisture cannot penetrate. This is similar to the polycomposite panel substrate proven in over four years of use in other TODCO doors, so you can be confident they will stand up to the day-in and day-out challenges every fleet faces.

PolarTek panels are filled with polyurethane foam, so they provide all of the K-Factor efficiency you have come to expect from TODCO insulated reefer doors. There are no thru rivets in the center of the panel to further prevent cold air loss, as well as provide a smooth surface for decals and painted graphics.

And PolarTek features the optional LifeGuard lock that allows the door to be opened from the inside, even when the door is padlocked and secured. The springs and counterbalance shaft are E-coated to protect against rust.



1332 Fairground Road East
Marion, Ohio 43302
(740) 383-6376

NOT JUST TOUGH...TODCO-TOUGH.

www.todco.com

POLARTEK™ REFRIGERATED DOOR

Polycomposite construction makes the door impervious to moisture. Smooth, high-quality finish makes painting optional.

Same headroom, less weight.


PolarTek door requires standard 9 inches of headroom, but weighs significantly less than other doors in its class.

No thru rivets on center hinges.

Eliminates cold air loss through conductivity, and gives the door a smooth surface for an automotive-quality paint finish and/or excellent decal adhesion.

Single counterbalance spring for effortless operation.

Standard bottom seal for thermal and weather protection.



Moisture resistant, thermal efficient polyurethane foam core. Foam creates thousands of air pockets to stop BTU loss, and adds strength and rigidity to each panel.

Unique panel joints designed to form a better thermal barrier.

Tough double-wall panels are extruded in one piece for added strength.

Thru rivets on end hinges put extra strength where needed. Single rubber seal prevents cold loss through rivet head, while optional dual-lip seal blocks cold loss from the rear.

For new orders and order inquiries, fax 1-800-24-TODCO (1-800-248-6326).

TODCO reserves the right to change product specifications at any time without notice.